



Specifications Philips LED Downlight  
Coreline DN142B Aluminium White  
19.2W 2300lm 60D - 840 Cool White |  
Cutout 200mm - IP54 - White Reflector

[View Product](#)

## General Information

|                      |                              |
|----------------------|------------------------------|
| SKU                  | 248723                       |
| EAN                  | 8720169502925                |
| Manufacturer Code    | 8720169502925                |
| Brand                | Philips                      |
| Manufacturer Name    | DN142B 20S/840 PSU-E WR IP54 |
| Budgetlight warranty | 5 Years                      |
| Average Lifetime (h) | 50000                        |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Tiltable                    | No              |
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x18            |
| Wattage                     | 19.2W           |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 840 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light Colour Options        | Single Color    |

|                       |                                             |
|-----------------------|---------------------------------------------|
| Beam Angle (degree)   | 60                                          |
| Luminous Flux (Lumen) | 2300lm                                      |
| Lumen per watt        | 120                                         |
| Powerfactor           | >0.95                                       |
| Unified Glare Rating  | < 25 - For hallways, staircases & elevators |
| Optische Afdekking    | PC (Polycarbonate)                          |
| Type product          | LED Downlight                               |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| EOC8                   | 50292500                      |
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-rating              | IP54                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Bedrijfstemperatuur    | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 6-pole] |
| Product Serie          | DN142B                        |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 105 |
| Diameter (mm) | 216 |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor



**Easy** return process

No Sensor



Long-life **LED solutions**